

www.blackoutcurtains.com

8527 Westmoreland, Suite 111 / Minneapolis, Minnesota 55426 / 866.BLACKOUT

Specifications for Blackout Curtain Fabric and Hardware

A. Manufacturer: www.blackoutcurtains.com

8527 Westmoreland, Suite 111

Minneapolis, Minnesota 55426 866.252.2568

B. Curtain Material and Fabrication:

1. The blackout curtain material is 100% blackout polyester. All Samples must be requested.
2. The curtain shall be sewn flat with 15% fullness. The seams shall be sewn with no raw edges visible. The curtain top shall be grommeted on 6" centers. The bottom edge shall have 2" double hem.
3. Double curtains installation (in specific uses) : Where (2) separate curtain panels meet they shall overlap each other approximately 24 inches.
4. Curtains shall be supplied with minimum 12 inch high front light-trap valance. The valance shall be made of the same blackout curtain materials, sewn flat (no fullness) with a sewn-on Velcro strip and self adhesive strip to be adhered to track face.
5. Blackout curtain must be flame-retardant materials. Fabric passes the flame resistance requirements specified by the State and be in accordance with the NFPA Standard No. 701-99 test methods 1 and 2. Submit certificate of passage to test.

C. Track Material and Assembly:

1. Track to be 29/32" X 11/16" x .050 extruded 6063-T-5, anodized aluminum. Inner surface is center ridge-grooved. Tracks can be bent or curved. Bends will be approx, 14: radius. The track shall also serve as an intergral part of the valance assembly. Supply with hook carriers, end-caps, knock-outs, and connectors, of the sleeve type. Carrier body and wheels of Celcon. Eye and hook of .093 bright basic wire, nickel plated.
2. Double curtains installation (in specific uses) :Provide (2) parallel tracks for double curtain installation.